EC-TYPE EXAMINATION CERTIFICATE

- Equipment and protective systems intended for use in potentially explosive atmospheres -Directive 94/9/EC
- (3) EC-Type Examination Certificate Number: KEMA 10ATEX0009 X Issue Number: 1
- (4) Equipment: Electric Actuator, Series ITQ
- (5) Manufacturer: i-Tork Controls Ltd.
- (6) Address: 74-6, Chunui-Dong, Wonmi-Gu, Bucheon SI, Kyeonggi-Do, Korea
 - 7) This equipment and any acceptable variation thereto is specified in the schedule to this contribate and the documents therein referred to.
- (8) KEMA Quality BV, notified body number 0344 in accordance with Article 9 of the Council Directive 948/EC of 23 March 1994, cartified and this equipment has been found to comply with the Essential Health and Sately Requirements relating to the design and construction of equipment and protective systems intended for use in optentially explosive emporpheres given in Annual II to the direction.

The examination and test results are recorded in confidential test report number 213129000.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

- EN 60079-0 : 2006 EN 60079-1 : 2007
- (10) If the sign "X" is placed after the cartificate number, it indicates that the equipment is subject to special conditions for safe use specified in the carbeilule to this cartification.
 (11) This EC-Type Examination Cartificate instens only to the despin, examination and tests of the specified equipment according to the Directive SeleCEC. Further requirements of the directive seek's to the impredictation proposed.
- supply of this equipment. These are not covered by this certificate.

 (12) The marking of the equipment shall include the following:



II 2 G Ex d IIB T4

This certificate is issued on April 29, 2010 and, as far as applicable, shall be revised before the date of cessation of presumption of conformity of (one of) the standards mentioned above as communicated in the Official Journal of the European Union.

KEMA Quality B.V

C.G. van Es Certification Manager

Page 1/3

*Integral publication of this certificate and adjoining reports is allowed. This Certificate may only be reproduced in its entirety and without any change.

KEMA Quality B.V. Utrachtseweg 310, 6812 AR Ambem P.O. Box 5185, 6802 ED Ambem The Netherlands T+31 26 3 56 20 00 F+31 26 3 52 58 00 www.kemaquality.com Registered Ambem 09085396



(13) SCHEDULE

(14) to EC-Type Examination Certificate KEMA 10ATEX0009 X Issue No. 1

(15) Description

The ITQ-Series of electric actuators are designed for quarter turn operating applications and include a worm gear assembly, manual handle and override, position indicator and an internal heater system.

The model code designation of the actuator is as follows:

ITQ-a3bcd

a = model name 0100, 0160, 0240, 0350, 0500, 0800, 1100, 2000, 3000, 6000, 9000

b = input voltage 1 = 110 Vac, 1 ph. 2 = 220 Vac, 1 ph.

4 = 380 Vac, 3 ph 5 = 440 Vac, 3 ph

7 = 24 Vdc

1 = PK 2 = CT

d = additional switch 0 = none

= additional switch 0 = none 1 = 2ALS 2 = 2ATS

Ambient temperature range -20 °C to +60 °C.

Electrical data

Voltage: 110/220 Vac, 1-ph, 50/60 Hz 380/440 Vac, 3-ph, 50/60 Hz

24 Vdc

Duty cycle: \$2-30 min, \$4-50 % (ITQ-0100 - ITQ-0350) \$2-20 min, \$4-30 % (ITQ-0500)

S2-20 min, S4-25 % (ITQ-0800 - ITQ-9000)

Motor power: 15 W (ITQ 0100) 40 W (ITQ 0160 - ITQ 0350)

90 W (ITQ 0500) 180 W (ITQ 0800 - ITQ 1100) 750 W (ITQ 2000 - ITQ 9000)

Installation instructions

The installation instructions provided by the manufacturer shall be followed in detail to assure safe operation of the equipment.

MEAN-P-Ex30 V1.0 Page 2/3



(13) SCHEDULE

(14) to EC-Type Examination Certificate KEMA 10ATEX0009 X

Issue No. 1

(16) Test Report

KEMA No. 213129000.

Special conditions for safe use

For details on the flamepaths the manufacturer shall be contacted.
 Fasteners with property class A2-50 are used.

(18) Essential Health and Safety Requirements

Covered by the standards listed at (9).

(19) Test documentation

As listed in Test Report No. 213129000.

MEAN-P-Ex30 V1.0 Page 3/3